

# Product Datasheet



## **VERSIO RECESSED**

## LED Panel


## Description:


Suitable for recessed mounting in unventilated or ventilated ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

## **Technical Features:**

Installation	: Recessed	Kelvin	: 3000-4000-5000-6500
Warranty	: 5 years	CRI	: >90
Lamp Type	: LED	LED Lifetime	: 80.000 h
Glass	: Difusser	Power Supply	: 110-240V 50-60Hz
IP	: 20	Op. Temp.	: -20°C / +45 °C
	1		

## Prometrical Data:





Colours

Chrome

White

## Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
RPG1	10	Versio Recessed Panel Gear 1	1250	300-300-50
RPG2	20	Versio Recessed Panel Gear 2	2500	300-600-65
RPG3	33	Versio Recessed Panel Gear 3	4125	600-600-65
RPG4	33	Versio Recessed Panel Gear 4	4125	300-1200-65
RPG5	56	Versio Recessed Panel Gear 5	7000	600-1200-65

## **Technical Options:**



\*Dimmer

\*Emergency Kits

#### Quality Certificiate:



- Tel : +90 (212) 798 3041 42
- Fax : +90 (212) 798 3043

Web : <u>www.entekled.com.tr</u>

ENTEK LED reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.

b